



GOTHAM²

S9GO01 HGO 201 BEIGE
S9GO05 HGO 205 GRAY - S9GO08 HGO 208 NERO



S9G001 • HGO201 BEIGE
24x24 in 60x60 cm

S9G005 • HGO205 GRAY
24x24 in 60x60 cm

S9G008 • HGO208 NERO
24x24 in 60x60 cm

Special Pieces



S8G001G • Step / HGO201 BEIGE
12x24 in 30x60 cm



S8G005G • Step / HGO205 GRAY
12x24 in 30x60 cm



S8G008G • Step / HGO208 NERO
12x24 in 30x60 cm



S8G001C • Pool Coping with full round edge / HGO201 BEIGE
12x24 in 30x60 cm



S8G005C • Pool Coping with full round edge / HGO205 GRAY
12x24 in 30x60 cm



S8G008C • Pool Coping with full round edge / HGO208 NERO
12x24 in 30x60 cm

THICKNESS	FREEZE / THAW	WATER ABSORPTION	RECOMMENDED USE	CHEMICAL/STAIN RESISTANCE	BREAKING STRENGTH	SLIP RESISTANCE
0.79" 20 mm	RESISTANT ASTM C 1026	~0,1% ASTM C 373		Class: A ASTM C 650 Class: A ASTM C 1378	≥3400 lbs. ASTM C 648	≥0.60 ANSI 137.1 (DCOF)

PACKAGING	24x24 in
Pcs.	66
Sq.Ft.	255.75
Lbs.	2380

SHADE VARIATION

LOW	MODERATE	HIGH	RANDOM



OFFICINE BONFIGLIOLI.IT



Del Conca USA, Inc. - 155 Del Conca Way - Loudon, TN 37774 - USA
Tel 865.657.3550 - Fax 865.657.3554
www.delconcausa.com - sales@delconcausa.com

